



# 50 TEX SLIP-RESISTANT ADDITIVE

PRODUCT DATA SHEET  
Edition 03/2018  
Version 001  
30000226

## PRODUCT DESCRIPTION

**50 TEX** is a stir-in additive that provides a slip-resistant texture to Simiron floor coatings. A longer lasting surface is created by this product's ability to resist chemicals and detergents.

**50 TEX** delivers a safer setting for home, commercial, and industrial settings. This additive works excellent for both interior and exterior surfaces and will not alter the color of the coating.

- Long-lasting
- Does Not Affect Topcoat Color
- Easy-To-Use
- Smooth, Walkable surface

## FEATURES & BENEFITS

- Add to paints, stains or sealers
- Add to latex-based, oil-based and epoxy coatings
- Easy surface cleaning
- Spherical-shaped particles provide a smoother feel to touch
- Does not increase material viscosity
- Stays suspended in coating

## JOBSITE TEST SECTION

Due to the difference in substrates, environments, and preparation methods always test the product in a small corner area before full application to determine adhesion and compatibility.

## LIMITATIONS

**SIMIRON 50 TEX** increases the coefficient of friction on the surface of a paint making the final coating slip-resistant, but due to its small particle size, it will not be skid-resistant. *Do not use on wood stains.*

## INSTRUCTIONS

Add contents of one **50 TEX** container into one gallon of a Simiron coating\* while mixing. **SIMIRON 50 TEX** should be mixed into the final topcoat. Mix well and apply with a roller. Occasionally stir product to keep material evenly suspended.

*\*Refer specific coating label and product data page for detailed product guidelines.*



**Corporate Office**  
SIMIRON  
32700 Industrial Drive  
Madison Heights, MI 48071  
(248) 686-3600 / (866) 515-8775

## RECOMMENDED USES

- Concrete and Masonry surfaces
- Inclined surfaces
- Driveways
- Garages
- Workshops
- Steps
- Patios
- Pool decks

## ORDERING INFORMATION

Clear	Item Number
3.2 oz	40002909

## TECHNICAL SERVICES

The information and recommendations set forth in this product data sheet are based on tests conducted by or on behalf of Simiron. The information and recommendations given here are subject to change and pertain to the product offered at the time of publication. Consult your Simiron representative to obtain the most recent product data sheet.

For technical assistance, call **1-248-686-3600** or visit [www.simiron.com](http://www.simiron.com)

## CAUTION

**⚠** Only apply when there is adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.**

## LIMITED WARRANTY

Seller's and manufacturer's only obligations shall be to replace such quantity of product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the applicator's inability to use the product for his/her intended use. The user assumes all risk and liability.

**Disclaimer:** All information provided by Simiron, Inc. concerning Simiron products, including but not limited to, any recommendations and advice relating to the application and use of Simiron products, is given in good faith based on Simiron's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Simiron's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Simiron's control are such that Simiron assumes no liability for the provision of such information, advice, recommendations or instructions related to its products. The use of Simiron product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s).

Simiron reserves the right to change the properties of its products without notice. All sales of Simiron product(s) are subject to its current terms and conditions of sale which are available by calling (866) 515-8775.