

MANUFACTURER:

SaverSystems

Richmond, IN 47374

800-860-6327

Fax: 765-935-4999

www.defywoodstain.com

DESCRIPTION

DEFY Extreme Wood Stain is an extremely durable synthetic-resin, semi-transparent wood finish that helps protect against the damaging effects of water, fungi, and UV radiation on exterior wood surfaces.

This V.O.C. compliant water-based product provides a beautiful matte finish, fortified with transparent "oxide" based Nano Particles. There are over 30 TRILLION nano particles per square inch that provide extreme protection for your wood by blocking out the sun's harmful UV rays, moisture and fungal growth.

USES

DEFY Extreme Wood Stain can be used on interior or exterior wood surfaces including: wood siding, log homes, decks, fences, shake shingles, outdoor wood furniture, pressure treated and all other natural wood surfaces.

ADVANTAGES

- Toughness and durability of "Nano Particle Technology"
- Protects wood from graying
- Penetrating finish resists peeling
- Soap and water clean-up

DIRECTIONS FOR USE

Weather Conditions: Surface and air temperatures should be between 45°F and 95°F. Avoid application in direct sunlight. Although surface may be slightly damp, do not apply to wet or water saturated surfaces, or when rain is expected within 12 hours.

Surface Preparation: Allow new wood to weather for three to six months to adequately dry out prior to application.

Strip: Do not use DEFY Extreme Wood Stain over painted or varnished surfaces. These surfaces must be stripped prior to application of the product. If sanding is necessary to remove older finishes, use a coarse grit sandpaper. Avoid using fine grit sandpapers as they can adversely affect the penetration of the stain.

Clean: All wood surfaces must be clean, porous, and dry before applying DEFY Extreme Wood Stain. Use DEFY Wood Cleaner to remove mill glaze, mildew, graying and other foreign matter that might block surface pores and interfere with product penetration. Rinse thoroughly with a garden hose or power washer (maximum 1200 p.s.i.). DEFY Wood Cleaner will darken redwood and some types of cedar; however, this darkening will disappear once the wood is treated with DEFY Wood Brightener.

Brighten: While surface is still wet from cleaning or stripping, use DEFY Wood Brightener to neutralize the wood, restore the wood to its natural color, and open the pores of the wood, allowing the stain to be more easily absorbed.

Water test: After allowing the wood to thoroughly dry from cleaning and brightening, sprinkle a few drops of water on the wood. It should soak in within a few seconds. If it doesn't, then do not apply the finish. The wood is either not dry enough or not porous enough to accept the finish correctly. Test a small area for color and appearance before starting general application to assure desired results.

APPLICATION

Mix well: Shake or stir contents before and periodically during use. To ensure absolute color uniformity from container to container, mix at least one third of the product from a used container with the contents of a new one. Do not thin product.

Protect adjacent areas: Use plastic, cardboard, and/or drop cloths to protect all adjacent non-targeted surfaces such as siding, windows, masonry, plant life, etc. from overspray and runoff. Immediately remove overspray from non-targeted areas with soap and water. Overspray that is allowed to dry will be difficult to remove; dried product cannot be removed from concrete and masonry.

Use the right equipment: Hand brushes should be high quality nylon or polyester. A deck brush or paint roller may also be used. If using an airless sprayer, use tips between .011 and .015, and use the lowest pressure that achieves a uniform spray pattern to minimize fogging and overspray. A pump-up sprayer may also be used. When spraying or rolling, always back brush to ensure a uniform application, and to break the surface tension of the wood so the stain will penetrate deeper, adhere better and last longer.

Decks: Start by applying DEFY Extreme Wood Stain to the railings, benches, and undersides of upper level decks (only one coat is required on undersides). Once underside is treated, immediately brush out all overspray, drips, etc. Treat horizontal surfaces last.

Horizontal surfaces: On horizontal cedar, mahogany, and other dense woods, apply only one coat of finish. For pressure treated lumber and other porous woods apply two coats, waiting approximately 20 minutes between coats. **It is very important to not let the first coat dry completely before applying the second coat.** Brush product into surface working out all drips, puddles, or areas of overspray before product dries. **Do not over apply finish.** To avoid the possibility of peeling, apply only as much finish as the wood can easily absorb. A sure indication of over application is a shiny appearance. Complete entire sections or to a natural break before allowing to dry. Never break in the middle of a board. Thoroughly coat the ends of boards or logs to prevent water penetration. All surface checks on logs should be thoroughly coated.

Vertical Surfaces: Start from the bottom and work up. Treat the entire length of a board before moving up. If necessary, brush or feather in to avoid lap marks. Brush in product before it dries and work out drips, runs, or overspray.

Wood shingles: Clean and test for porosity. Apply two, heavy saturation coats. Depending on porosity, a third coat may be necessary to achieve total saturation. Back brush between coats to ensure a uniform application. Brush out all drips and puddles. To avoid restart lines, start at the bottom and treat entire length before moving up.

Drying time: To touch, two to six hours depending on temperature and humidity. Allow 24 hours for deck to completely cure before using. High humidity and lower temperatures can greatly increase dry time.

Coverage: With two coats, one gallon of DEFY Extreme Wood Stain will cover approximately 100 - 150 sq. ft., depending on wood texture and porosity.

CLEAN UP

Clean tools and equipment immediately after each use with soap and water.

CAUTIONS

Keep out of reach of children. May cause an allergic skin reaction. Avoid breathing fumes, dust, mist, spray, vapor. Wear eye protection, protective clothing, and protective gloves. Dispose of contents/container to comply with applicable local, national and international regulation. Close container tightly after each use. Do not re-use containers.

FIRST AID

If inhaled: In all cases of doubt, or when symptoms persist, seek medical advice. Move the affected person away from the contaminated area and into the fresh air.

If swallowed: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting unless directed to do so by a physician. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Immediately call a POISON CENTER or doctor/physician.

For skin contact: Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Obtain medical attention if irritation persists.

For eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

For additional information for this product, consult the Safety Data Sheet available at www.defywoodstain.com.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Available in one- and five-gallon recyclable plastic containers.

TRANSPORT AND HANDLING

DEFY Extreme Wood Stain is not considered hazardous under Department of Transportation regulations. Do not stack pallets.

Keep from freezing.

MAINTENANCE

Occasional cleaning with mild detergent and water will generally restore treated surfaces to their original appearance. DEFY Extreme Wood Stain must be re-coated within 24 months, or when graying initially starts to appear. Prior to application, brightening with DEFY Wood Brightener is recommended to insure uniform color.

PHYSICAL PROPERTIES

COMPOSITION..... A blend of synthetic resins with nano-particle technology
SOLVENT..... Water
WEIGHT..... (8.4 lb/gal)
VOC CONTENT..... <100 g/L
SHELF LIFE..... 36 months
FREEZE THAW STABILITY..... No

TECHNICAL DATA

Test Results: ASTM D5401: Percent water absorption on wood treated with DEFY<1%.

ASTM G53: Accelerated weathering (QUV) 2,500 hours. Excellent color retention; no loss in water repellency.

Outdoor Exposure: Indiana and Florida test fences. No graying, no loss in water repellency.